IARC Library: 03.35.00 SC 2013 Concrete Coating 03.35.00 2013

PRODUCT	TYPE OF PRODUCT	Color Conditioned Concrete
INFORMATION		Scofield Systems
	PRODUCT/COLLECTION NAME	Chromix admixtures, Lithocrome hardener
	DESCRIPTION	Engineered systems for enhancing architectural concrete
MATERIAL FEEDSTOCK	MATERIAL CONTENT	Hard aggregates, powder
MATERIAL TELDSTOCK	RECYCLED CONTENT %	Powder contain approximately 99% recycled material
	HEOTOLED CONTENT /	95% recycled material overall
	RAPIDLY RENEWABLE CONTENT	
	%	None
	HARMFUL ADDITIVES	Hardening powder
	HARMFUL EMISSIONS	N/A
	EMISSION STRENGTH OVER TIME	N/A
	TREATMENTS	Powder
MANUFACTURING	MANUFACTURING PROCESS	Energy intensive-
	HARMFUL EMISSIONS	Information not found
	LOCATION OF MANUF. PLANT	Douglasville, GA
	TESTS/CODES	High Compressive Strength
	3 RD PARTY CERTIFICATION	USGBC Member
INSTALLATION	INSTALLATION PROCEDURE	Pour in place
	INSTALLATION ADHESIVES	None
	UNIT COST	Varies by productLess than \$1.00 per square foot
	LIFE CYCLE ANALYSIS	Low VOC, non-acidic, waterborne, environmentally sound green building
		material.
	END OF SERVICE LIFE	Very long service life, does not need to be replaced
MISC. PROPERTIES	QUALITIES/PROPERTIES OF	A rich, diverse palette of concrete colors
	PRODUCT	Evenly dispersed, consistent, streak-free concrete color throughout the
		concrete mix
		Repeatability batch-to-batch and project-to-project Superior, non-fading, permanent concrete coloring
		Increased concrete strength at all ages.
	MISC. COMMENTS	
	CONTRIBUTION TO LEED POINTS	Sustainable Sites Credit 7.1 Heat Island Effect, low SRI value
		It may contribute to earning LEED credits for Indoor Environmental
		Quality, 4.2 Low Emitting Materials, Paints & Coatings based on low
		contribution of VOC.
COMPANY PROFILE	GREEN PHILOSOPHY	The adoption of Green building initiatives perfectly complements
		Scofield's commitment to environmental stewardship. Scofield continually
		researches and develops lasting, reliable, eco-friendly systems while
		providing professional consultation, technical assistance and product
		training to the entire chain of industry professionals.
	CONTACT	1-800-800-9900
		L M Sasfield Company
		L. M. Scofield Company 4155 Scofield Rd.
		Douglasville, GA 30134
		Phone: (770) 920-6000
		Fax: (770) 920-6060
MAINTENANCE	AFTER INSTALLATION	Wash 50/50 water vinegar solution
		riacit estes frator fillogal solution