

<b>PRODUCT INFORMATION</b>	<b>TYPE OF PRODUCT</b>	Accent beam system- see also 9.57.00, 6.40.23
	<b>COMPANY NAME</b>	Rulon
	<b>PRODUCT/COLLECTION NAME</b>	Accent Beams
	<b>DESCRIPTION</b>	Accent beams are a cost effective way of enhancing a ceiling without the expense encountered with traditional field built assemblies. Structural features can be hidden inside the beams making high-end designs very affordable, due to quick and easy installation.
<b>MATERIAL FEEDSTOCK</b>	<b>MATERIAL CONTENT</b>	Prime grade, all-natural [specie] [wood OR veneer on core board] with a [selected] finish. With custom stains, clear sealers or color treatments are water-based, contain no solvents and emit no VOC's.
	<b>RECYCLED CONTENT %</b>	0%
	<b>RAPIDLY RENEWABLE CONTENT %</b>	None
	<b>HARMFUL ADDITIVES</b>	No solvents in finishes
	<b>HARMFUL EMISSIONS</b>	Glues and finishes are water-based and Low-VOC. 100% water-based Low-VOC finishing process. No added Urea Formaldehyde cores are used for veneered products.
	<b>EMISSION STRENGTH OVER TIME</b>	N/A
<b>MANUFACTURING</b>	<b>TREATMENTS</b>	Water-based finishes and glues
	<b>MANUFACTURING PROCESS</b>	New state-of-the-art facility is designed to reduce energy consumption and advanced sawdust collection system allows maximum amount of waste to be donated to local business for use as biofuel.
	<b>HARMFUL EMISSIONS</b>	Unknown
	<b>LOCATION OF MANUF. PLANT</b>	St. Augustine, Florida
	<b>TESTS/CODES</b>	ASTM E-84 Class 1 or A fire retardance
<b>INSTALLATION</b>	<b>3<sup>RD</sup> PARTY CERTIFICATION</b>	FSC certified
	<b>INSTALLATION PROCEDURE</b>	Manufactured to be attached to the ceiling or deck above. Can be suspended using threaded rod or 12-gauge hanger wire. Wood should be allowed to acclimate to the room 72 hours prior to installation.
	<b>INSTALLATION ADHESIVES</b>	No adhesives
	<b>UNIT COST</b>	N/A
	<b>LIFE CYCLE ANALYSIS EXTRACTION</b>	Enduring product selection should lead to long lifespan.
<b>MISC. PROPERTIES</b>	<b>END OF SERVICE LIFE</b>	Components may be individually recycled.
	<b>QUALITIES/PROPERTIES OF PRODUCT</b>	Can be made in flat, vaulted, or radius forms in depth and thickness to accommodate each ceiling installation. Eight standard species available.
	<b>MISC. COMMENTS</b>	100% pre-consumer recycled wood fiber core board is used for veneered products.
<b>COMPANY PROFILE</b>	<b>CONTRIBUTION TO LEED POINTS</b>	MR 4.1, 4.2, 5.1, 5.2, 7 and EQ 4.1, 4.2, 4.4
	<b>GREEN PHILOSOPHY</b>	Through new and innovative practices Rulon, as the leading manufacturer in suspended wood ceiling and acoustical wood wall systems, sets the standard for green manufacturing processes above the minimum regulations.
	<b>CONTACT</b>	www.rulonco.com 2000 Ring Way Rd. St. Augustine, FL 32092 1-800-227-8566
<b>MAINTENANCE</b>	<b>AFTER INSTALLATION</b>	