PROPULOT	TYPE OF PROPUST	
PRODUCT INFORMATION	TYPE OF PRODUCT	Wood Danel Custom, one also 00 74 10
INFORMATION	COMPANY NAME	Wood Panel System- see also 09.74.13 Rulon
	PRODUCT/COLLECTION NAME	
	DESCRIPTION	Flat Veneered panels
	DESCRIPTION	Panels manufactured in a number of configurations and veneers, either
MATERIAL FEFROTOCK	MATERIAL CONTENT	flat or curved panels. Prime grade, all-natural [specie] [wood OR veneer on core board] with a
MATERIAL FEEDSTOCK	MATERIAL CONTENT	[selected] finish. With custom stains, clear sealers or color treatments are
		water-based, contain no solvents and emit no VOC's.
	RECYCLED CONTENT %	0%
	RAPIDLY RENEWABLE CONTENT	None
	%	None
	HARMFUL ADDITIVES	No solvents in finishes
	HARMFUL EMISSIONS	Glues and finishes are water-based and Low-VOC. 100% water-based
	HARMFUL EMISSIONS	Low-VOC finishing process. No added Urea Formaldehyde cores are
		used for veneered products.
	EMISSION STRENGTH OVER TIME	N/A
	TREATMENTS	Water-based finishes and glues
MANUFACTURING	MANUFACTURING PROCESS	New state-of-the-art facility is designed to reduce energy consumption
MANOFACTORING	WANDFACTORING PROCESS	and advanced sawdust collection system allows maximum amount of
		waste to be donated to local business for use as biofuel.
	HARMFUL EMISSIONS	Unknown
	LOCATION OF MANUF. PLANT	St. Augustine, Florida
	TESTS/CODES	ASTM E-84 Class 1 or A fire retardance
	3 RD PARTY CERTIFICATION	FSC certified
INSTALLATION	INSTALLATION PROCEDURE	Installed into T-bar grid. Torsion Spring or Saddle Clip suspension into
INSTALLATION	INSTALLATION PROCEDORE	heavy duty T-bar grid. Z-Clips and direct screw attachment to heavy duty
		T-bar grid or aircraft cable available. Wood should be allowed to acclimate
		to the room 72 hours prior to installation.
	INSTALLATION ADHESIVES	No adhesives
	UNIT COST	N/A
	LIFE CYCLE ANALYSIS	Enduring product selection should lead to long lifespan.
	EXTRACTION	
	END OF SERVICE LIFE	Components may be individually recycled.
MISC. PROPERTIES	QUALITIES/PROPERTIES OF	A variety of wood veneers, both domestic and exotic, give the architect
	PRODUCT	virtually unlimited design freedom. Eight standard species available.
	MISC. COMMENTS	100% pre-consumer recycled wood fiber core board is used for veneered
		products.
	CONTRIBUTION TO LEED POINTS	MR 4.1, 4.2, 5.1, 5.2, 7 and EQ 4.1, 4.2, 4.4
COMPANY PROFILE	GREEN PHILOSOPHY	Through new and innovative practices Rulon, as the leading manufacturer
		in suspended wood ceiling and acoustical wood wall systems, sets the
		standard for green manufacturing processes above the minimum
		regulations.
	CONTACT	www.rulonco.com
		2000 Ring Way Rd.
		St. Augustine, FL 32092
		1-800-227-8566
<u>MAINTENANCE</u>	AFTER INSTALLATION	