

PRODUCT INFORMATION	TYPE OF PRODUCT	Wood Ceiling System- see also 09.54.26, 06.44.00
	COMPANY NAME	Rulon
	PRODUCT/COLLECTION NAME	Linear Wood Ceiling System
	DESCRIPTION	Open or closed shiplap style wood planking using cliprail system, which eliminates heavy metal framing and support wood needed to hold nailed-in-place boards
MATERIAL FEEDSTOCK	MATERIAL CONTENT	Prime grade, all-natural [specie] [wood OR veneer on core board] with a [selected] finish. With custom stains, clear sealers or color treatments are water-based, contain no solvents and emit no VOC's.
	RECYCLED CONTENT %	0%
	RAPIDLY RENEWABLE CONTENT %	None
	HARMFUL ADDITIVES	No solvents in finishes
	HARMFUL EMISSIONS	Glues and finishes are water-based and Low-VOC. 100% water-based Low-VOC finishing process. No added Urea Formaldehyde cores are used for veneered products.
	EMISSION STRENGTH OVER TIME TREATMENTS	N/A Water-based finishes and glues
MANUFACTURING	MANUFACTURING PROCESS	New state-of-the-art facility is designed to reduce energy consumption and advanced sawdust collection system allows maximum amount of waste to be donated to local business for use as biofuel.
	HARMFUL EMISSIONS	Unknown
	LOCATION OF MANUF. PLANT	St. Augustine, Florida
	TESTS/CODES	ASTM E-84 Class 1 or A fire retardance, ASTM C-423 sound absorption
INSTALLATION	3RD PARTY CERTIFICATION	FSC certified
	INSTALLATION PROCEDURE	For ceilings, T-bar grid is suspended, panels installed by direct screw attachment to T-bar at woodbacker strips, or snapped to T-bar carriers using woodbacker clips. Wall mounting also available. Wood should be allowed to acclimate to the room 72 hours prior to installation.
	INSTALLATION ADHESIVES	No adhesives
	UNIT COST	N/A
	LIFE CYCLE ANALYSIS EXTRACTION	Made of ¾" thick solid hardwood for longevity.
MISC. PROPERTIES	END OF SERVICE LIFE	Components may be individually recycled.
	QUALITIES/PROPERTIES OF PRODUCT	The installer simply suspends the cliprails from the deck then snaps the light weight linear boards into place - a cost savings in labor. Beauty of wood with modern designs. Eight standard species available.
	MISC. COMMENTS	100% pre-consumer recycled wood fiber core board is used for veneered products.
COMPANY PROFILE	CONTRIBUTION TO LEED POINTS	MR 4.1, 4.2, 5.1, 5.2, 7 and EQ 4.1, 4.2, 4.4
	GREEN PHILOSOPHY	Through new and innovative practices Rulon, as the leading manufacturer in suspended wood ceiling and acoustical wood wall systems, sets the standard for green manufacturing processes above the minimum regulations.
COMPANY PROFILE	CONTACT	www.rulonco.com 2000 Ring Way Rd. St. Augustine, FL 32092 1-800-227-8566
	MAINTENANCE	AFTER INSTALLATION 1 year warranty