IAR Library: 09.30.23 Oc 2007 Glass Tile 09.30.23 2007

PRODUCT	TYPE OF PRODUCT	
INFORMATION		Glass Tile
	COMPANY NAME	Oceanside Glasstile
	PRODUCT/COLLECTION NAME	A
	DESCRIPTION	Over 40 colors and three finishes: Iridescent, Non-Iridescent, and Matte in all of our glass tile lines. Freeze/thaw resistant, Oceanside Glasstile is used in both outdoor and interior design applications, including kitchen backsplashes, bathrooms, fireplace surrounds, and feature walls. Our products are also ideal for submerged applications such as pools, fountains and spas.
MATERIAL FEEDSTOCK	MATERIAL CONTENT	Made from silica sand and 86% recycled material, including over 2 million pounds each year of glass from curbside recycling programs. Oceanside also uses recycled glass that is trimmed during the handcrafting process.
	RECYCLED CONTENT %	86% recycled material
	RAPIDLY RENEWABLE CONTENT	
	%	None
	HARMFUL ADDITIVES	None
	HARMFUL EMISSIONS	None
	EMISSION STRENGTH OVER TIME	None
	TREATMENTS	none
MANUFACTURING	MANUFACTURING PROCESS	Cullet, post industrial glass and silica sand are combined with earth
MANUFACTURING		oxides for color to create proprietary glass formulas. The batch mixture is heated in gas-fired furnaces at approx. 23)) F. Once glass is a molten consistency, it is hand ladled into iron molds, slowly cooled, handcut, and trimmings are recycled.
	HARMFUL EMISSIONS	n/a
	LOCATION OF MANUF. PLANT	Carlsbad, CA; Tijuana, Mexico
	TESTS/CODES	n/a
	3 RD PARTY CERTIFICATION	none
INSTALLATION	INSTALLATION PROCEDURE	Due to the translucent nature of glass, the color of the bonding material will impact the ultimate look of the tile. We recommend the use of specific white bonding mortars; some mixed with specific latex admix. See the following list for required thin-sets and follow manufacturer's recommended cure times for all setting materials. Pools, spas and all submerged applications require a minimum 21-day cure time after grouting and before submersion or exposure to heavy water use. Although we require the use of the highest performing setting materials for installing our products, occasionally, due to the transparent and/or light translucent nature of some of our products, visible effects, also known as "Ghosting," may occur behind the glass. This is a normal occurrence and should not be considered a manufacturing problem with the glass tile. Acceptable Setting Systems (WHITE)
		 Custom building ProductS: MegaFlex Crack Prevention Mortar. Custom building ProductS: MegaLite Crack Prevention Mortar. Flextile: 52 Versatile Floor Mortar. HydroMent: ReFlex Ultra-Premium Latex-Modified Thin Set Mortar. KeraKoll: H40 Tenax Single Component Thin-Set. laticrete: 254 Platinum Multipurpose Thin-Set Mortar. MaPei: Kerabond Premium Dry-Set Mortar (KER 102) mixed with Keralastic Mortar Additive (KER 310) MaPei: Adesilex P10 mixed with Keraply mortar additive. tec (H.b. Fuller): Super Flex Premium Performance Universal Latex-Modified Thin-Set Mortar. use a clean, soft cloth. Acceptable Grouts We recommend standard sanded grout products. Custom building Products: Polyblend Sanded Tile Grout Flextile: 600 Polymer Sanded Floor Grout HydroMent: Sanded Ceramic Tile Grout

i -		
		KeraKoll: Fugabella 2-12
		 laticrete: 1500 Series Tile Grout or equivalent
		 MaPei: Ker 200 Series and Ker 700 Series Ultra/Color
		 tec: AccuColor Premium Sanded Tile Grout
	UNIT COST	Varies
	LIFE CYCLE ANALYSIS	n/a
	END OF SERVICE LIFE	n/a
MISC. PROPERTIES	QUALITIES/PROPERTIES OF	
	PRODUCT	Strong building material – breaking strength approx. 900 lbs per sq inch
	MISC. COMMENTS	A
	CONTRIBUTION TO LEED POINTS	MR c 4 Recycled Content
COMPANY PROFILE	GREEN PHILOSOPHY	Respect for the environment is essential to our company philosophy. All
		Oceanside Glasstile is made from silica sand; an abundant natural
		resource with many colors using up to 86 percent recycled material.
		Annually, we use more than two million pounds of glass from curbside
		recycling programs, turning waste that would otherwise end up in landfills
		into expressive and sustainable design materials.
	CONTACT	Oceanside Glasstile World Headquarters
		2293 Cosmos Court
		Carlsbad, CA 92011
		760-929-4000
		info@glasstile.com
		Traditions in Tile
		2201-112 Brentwood Rd.
		Raleigh, NC 27604
		Tel: 919.871.0203
		www.traditionsitile.com
		www.glasstile.com
MAINTENANCE	AFTER INSTALLATION	Warm water and liquid dish soap or a neutral pH cleaner.
		 Tubs and showers: DESCUM Soap Scum Remover & Renovator.
		 Pools and water features: Descale-It Pool & Spa Cleaner.