

PRODUCT INFORMATION	TYPE OF PRODUCT	Acoustical Ceilings
	COMPANY NAME	Hunter Douglas Contract
	PRODUCT/COLLECTION NAME	Techstyle® Ceilings E
	DESCRIPTION	Techstyle® acoustical ceiling panels and wall panels offer unprecedented performance, accessibility, and customization. Available in a wide variety of colors, sizes from 2' x 2' to 4' x 6', and several installation options.
MATERIAL FEEDSTOCK	MATERIAL CONTENT	Fiber Glass Mat Formaldehyde-free, Thermoplastic co-polyester, and Thermally point-bonded Polyester Non-woven
	RECYCLED CONTENT %	10% Pre-Consumer Recycled Content
	RAPIDLY RENEWABLE CONTENT %	80.0%
	HARMFUL ADDITIVES	None
	HARMFUL EMISSIONS	VOC Level (mg/m2h): 0.22
	EMISSION STRENGTH OVER TIME	None
	TREATMENTS	Not Expressed
MANUFACTURING	MANUFACTURING PROCESS	Melting, Forming into fibers, Continuous-filament process, Staple-fiber process, Chopped fiber, Glass wool, Protective coatings, and Forming into shapes
	HARMFUL EMISSIONS	Not expressed
	LOCATION OF MANUF. PLANT	Thornton, CO 80241
	TESTS/CODES	Moisture Resistance: Resistant to 95% humidity in 104 F temperature Fungal Resistance: Resistance (ASTM C 1338) Surface Burning Class: A (1) (ASTM E 84) (ASTME 1264) Flame <25 Smoke <50 Light Reflectance: LR-1 (77%) (ASTM E 1477) (White only) MEA: Acceptance (376-02-M) ICC: Approved
	3RD PARTY CERTIFICATION	GREENGUARD Children and Schools SM Certified for Indoor Air Quality (IAQ)
	INSTALLATION	http://assets.hunterdouglascontract.com/documents/ceilings/acousticalsolutions/classic/Installation_Instuct_2008.pdf
INSTALLATION	INSTALLATION ADHESIVES	N/A
	UNIT COST	A
	LIFE CYCLE ANALYSIS EXTRACTION	Durable panels ensure long product lifespan and maximize sustainability
	END OF SERVICE LIFE	Lightweight product (0.30 lb/sf) means less landfill waste at end of product life 100% Recyclable
	MISC. PROPERTIES	QUALITIES/PROPERTIES OF PRODUCT
MISC. COMMENTS		The Integrated Solutions system complements the clean, monolithic appearance for which Techstyle Acoustical Ceilings is known, by organizing light fixtures, diffusers and other penetrations into neat 6" strips that fit precisely between panels. Engineered for easy installation, the system offers a wide range of fixture spacings and panel sizes to accommodate a variety of configurations. Partnerships with leading fixture manufacturers make integration easy.
CONTRIBUTION TO LEED POINTS		NC 2.2 – EQ 4.2
COMPANY	GREEN	Hunter Douglas' commitment to sustainability and responsible development is evidenced by our continuous efforts to address environmental concerns, improve production processes, eliminate

PROFILE	PHILOSOPHY	waste and reduce maintenance.
	CONTACT	One Hunter Douglas Circle Thornton, CO 80241 866.556.1235
MAINTENANCE	AFTER INSTALLATION	If additional cleaning is needed, a moistened wipe (baby wipe) may be used. Wipe gently. A dry sponge will also work well. The dirty area may be lightly vacuumed. For best results, replace the vent filters regularly.