

IARc Library: 09.60.00 Brochures

Cork flooring

09.60.00

2012

PRODUCT INFORMATION	TYPE OF PRODUCT	Cork Flooring
	COMPANY NAME	Globus Cork
	PRODUCT/COLLECTION NAME	Tiles and Floating Floor
	DESCRIPTION	<ul style="list-style-type: none"> * Bold exclusive colours * Cork tile sizes from 4"x 4" to 18"x 36" * Wide variety of tile pattern cuts * Commercial cork flooring finishes * Geometric inset cork floor borders * Beveled edge cork tiles * Pre-glued and pre-finished cork tiles * Pre-finished cork floating floor panels * Custom colouring and sizing available
MATERIAL FEEDSTOCK	MATERIAL CONTENT	Cork, Fiberboard core
	RECYCLED CONTENT %	95% recycled post industrial waste
	RAPIDLY RENEWABLE CONTENT %	100%
	HARMFUL ADDITIVES	none
	HARMFUL EMISSIONS	No VOCs
	EMISSION STRENGTH OVER TIME	
	TREATMENTS	Not specified
MANUFACTURING	MANUFACTURING PROCESS	More than 10% of the finished product is extracted, processed and manufactured within the 500 mile limit and meets this credit requirement. Our regional area extends from Toronto to Raleigh NC to mid Ohio.
	HARMFUL EMISSIONS	none
	LOCATION OF MANUF. PLANT	n/a
	TESTS/CODES	ASTM, DIN
	3RD PARTY CERTIFICATION	Top 10 Manufacturer NYIRN 2007, Green Spec listed, MVP 2005 Hanley Wood, 2009 Nominee Green Log, 2005 ADEX Platinum, USGBC
INSTALLATION	INSTALLATION PROCEDURE	<p>-Cork Tiles: A. Install in accordance with manufacturer's instructions. B. Review and shuffle tiles before beginning the installation. C. Adhere cork tile using a latex, water-based contact adhesive formulated especially for cork tiles. Tiles are pre-glued from the factory and the matching adhesive must be evenly applied to the subfloor during installation. Adhesive to be applied to subfloor with a roller, not a trowel. Tiles must be hit with a rubber mallet after installation to ensure positive contact. D. Tiles have 3 factory applied coats of finish. Final finish with a water-based varnish formulated especially for cork. Apply a final commercial-grade finish coat after tile installation with a roller or paint pad.</p> <p>-Floating Floor: A. Install in accordance with manufacturer's instructions. B. Review and shuffle planks before beginning the installation. C. Begin in the corner of a room. Place the plank 1/2 inch (13mm) away from both walls at the corner D. Make the first long row of flooring in the room with the planks locked short end to short end, not side to side. E. Snap subsequent planks into the end of the previous until it locks flat and tight with no gap. Do not hammer directly on the clicking ridges or the cork as they will break. F. At row ends where cuts are required, planks may be cut using a hand saw, table saw or circular saw. G. Tiles have 3 factory applied coats of finish. Final finish with a water-based varnish formulated especially for cork. Apply a final commercial-grade finish coat after tile installation.</p>
	INSTALLATION ADHESIVES	Specified by installer
	UNIT COST	varies
	LIFE CYCLE ANALYSIS	n/a
	END OF SERVICE LIFE	>5 years under normal wear
		QUALITIES/PROPERTIES OF PRODUCT
MISC. PROPERTIES	MISC. COMMENTS	none

	CONTRIBUTION TO LEED POINTS	Credits MR 4.1 and 4.2: Certification letter indicating percentages by weight of post-consumer and pre-consumer recycled content for products having recycled content. Credit MR 5: Certification letter documenting that the Project location is within 500 miles (804 km) of material manufacturing location. Credit MR 6: Certification letter documenting the renewal duration of the material specified.
COMPANY PROFILE	GREEN PHILOSOPHY	Maintains green philosophy through sustainable harvesting, manufacturing and recycling practices.
	CONTACT	Phone: (718) 742-7264 Email: info@corkfloor.com Fax: (718) 742-7265 Mail: 741 E. 136th Street Bronx, NY 10454 USA
MAINTENANCE	AFTER INSTALLATION	Mop, vacuum