

PRODUCT INFORMATION	TYPE OF PRODUCT	Laminate Flooring
	COMPANY NAME	Wilsonart Flooring
	PRODUCT/COLLECTION NAME	Red Label, Estate Plus, Classic
	DESCRIPTION	Flooring and tile options is a variety of styles and colors that are easy to clean and install
MATERIAL FEEDSTOCK	MATERIAL CONTENT	Flooring contains wood fiber, Formaldehyde Resins, and adhesives Wilsonart BlueFashion Adhesive contains Vinyl Acetate Polymers, water and surfactant
	RECYCLED CONTENT %	100% of wood fiber in the high density fiber board is comprised of by products from the milling of dimensional lumber and plywood. Product packaging is made from 45% post consumer recycled fiber and uses about 45% less material than virgin timber.
	RAPIDLY RENEWABLE CONTENT %	n/a
	HARMFUL ADDITIVES	n/a
	HARMFUL EMISSIONS	VOC <20g/L
	EMISSION STRENGTH OVER TIME	n/a
	TREATMENTS	n/a
MANUFACTURING	MANUFACTURING PROCESS	Multiple manufacturing plans, also produces and distributes own brand of adhesive
	HARMFUL EMISSIONS	n/a
	LOCATION OF MANUF. PLANT	many
	TESTS/CODES	many
	3RD PARTY CERTIFICATION	ASTM E 1333 (Formaldehyde Release) < 0.10 ppm free formaldehyde Greenguard Certification Certified
INSTALLATION	INSTALLATION PROCEDURE	Tap-N-Lock Technology Installation System. Installed from right to left as a floating floor, meaning no adhesives or nails are used.
	INSTALLATION ADHESIVES	In wet areas, extreme climates or areas with heavy objects, Wilsonart BlueFusion Adhesive is used over the entire floor.
	UNIT COST	varies
	LIFE CYCLE ANALYSIS	n/a
	END OF SERVICE LIFE	n/a
MISC. PROPERTIES	QUALITIES/PROPERTIES OF PRODUCT	R-values for products and components between 0.04 – 0.58 ft ² ·hr·°F/Btu
	MISC. COMMENTS	A
	CONTRIBUTION TO LEED POINTS	Contributes to LEED-CI
COMPANY PROFILE	GREEN PHILOSOPHY	Bulk transport via train cuts down on vehicle emissions. Melamine treated overlay scrap is recycled into molding compounds used in common molded plastics.
	CONTACT	Wilsonart International, Inc. 2400 Wilson Place P.O. Box 6110 Temple, Texas 76503-6110 1-800-433-3222 www.wilsonart.com
MAINTENANCE	AFTER INSTALLATION	Clean with company cleaners, water and soap