

PRODUCT INFORMATION	TYPE OF PRODUCT	Bamboo Flooring
	COMPANY NAME	Smith and Fong Plyboo
	PRODUCT/COLLECTION NAME	Plyboo Strand, Dura Palm, Plyboo Bamboo flooring, Neapolitan Flooring, Plyboo squared
	DESCRIPTION	
MATERIAL FEEDSTOCK	MATERIAL CONTENT	Plyboo Strand – 100% Bamboo Dura Palm – 100% Coconut palm lumber Plyboo Bamboo Flooring – 100% Bamboo Neapolitan Flooring – 100% Bamboo Plyboo Squared – 100% Bamboo
	RECYCLED CONTENT %	No recycled content
	RAPIDLY RENEWABLE CONTENT %	Bamboo is a rapidly renewable material This is in all except – Durapalm Flooring The material in this product comes from well-managed forests, independently certified in accordance with the rules of the Forest Stewardship Council.
	HARMFUL ADDITIVES	No added Urea Formaldehyde Stain
	HARMFUL EMISSIONS	all Plyboo products are tested for emissions by an independent, third party lab located in the United States. In late 2007 the company began converting its plants to urea formaldehyde (UF)-free manufacturing processes, and UF-free PlybooPure flooring is now available throughout the North American market and is the heart of the Plyboo product line
	EMISSION STRENGTH OVER TIME TREATMENTS	N/A Stain, polyeruthane
MANUFACTURING	MANUFACTURING PROCESS	All are made from the Moso species of bamboo, which grows to maturity in five to six years with a height of over 40 feet and a diameter of more than six inches
	HARMFUL EMISSIONS	
	LOCATION OF MANUF. PLANT	601 Grandview So. San Francisco CA 94080
	TESTS/CODES	Test surface burning in accordance with ASTM E 84 SW-COC-003124 The material in this product comes from well-managed forests, independently certified in accordance with the rules of the Forest Stewardship Council.
	3RD PARTY CERTIFICATION	All Plyboo products already comply with the California Air Resources Board's (CARB) strictest formaldehyde regulations for composite panels, and many can contribute to the U.S. Green Building Council's LEED®
INSTALLATION	INSTALLATION PROCEDURE	Subfloor must be: • Structurally sound • Clean: Thoroughly swept and free of all debris • Level: Flat to 3/16" per 10-foot radius • Dry: Subfloor must remain dry year-round. Moisture content of wood subfloor must not exceed 12%; concrete moisture content must not exceed 3 lbs as tested using the calcium chloride test.
	INSTALLATION ADHESIVES	Bostik's Best Urethane Adhesive, Bostik's TKO, or the Mapei 980 or 990 are our recommended adhesives. Read adhesive instructions carefully for proper trowel size and adhesive set time. Never use the "wet lay" or "loose lay" method of installing. This is when you install the flooring immediately after spreading adhesive. This method will trap moisture under the floor and could cause the flooring to warp.
	UNIT COST	A
	LIFE CYCLE ANALYSIS EXTRACTION	N/A
	END OF SERVICE LIFE	N/A
MISC. PROPERTIES	QUALITIES/PROPERTIES OF PRODUCT	Dimensional stability 80%-20% relative humidity Rapidly renewable resource
	MISC. COMMENTS	A

	CONTRIBUTION TO LEED POINTS	MR 6: Rapidly Renewable Materials (all but Durapalm Flooring) EQ 4.4: Low-Emitting Materials (no added urea-formaldehyde)
COMPANY PROFILE	GREEN PHILOSOPHY	Smith & Fong Co. is the manufacturer of Plyboo®, the most respected name in bamboo plywood and bamboo flooring, and Durapalm®, an exotic and beautiful range of flooring and plywood derived from palms. Smith & Fong offers the world's only formaldehyde-free FSC-certified bamboo, and the company's California Section 01350-compliant plywood and flooring are found in design-rich commercial and residential environments worldwide, where sustainability meets innovation.
	CONTACT	For architectural samples, please call 866-835-9859, e-mail sales@plyboo.com, or use our online form. www.plyboo.com
MAINTENANCE	AFTER INSTALLATION	none