

<b>PRODUCT INFORMATION</b>	<b>TYPE OF PRODUCT</b>	Cork Flooring
	<b>COMPANY NAME</b>	DuroDesign
	<b>PRODUCT/COLLECTION NAME</b>	Cork Flooring Collection 2005-06
	<b>DESCRIPTION</b>	DuroDesign offers cork flooring in 54 colors and six patterns for an incredible selection and is available in either glue-down cork tiles or click-together floating floor planks.
<b>MATERIAL FEEDSTOCK</b>	<b>MATERIAL CONTENT</b>	100% cork
	<b>RECYCLED CONTENT %</b>	100% post-industrial recycled content from wine-stopper production.
	<b>RAPIDLY RENEWABLE CONTENT %</b>	100% renewable resource harvested as bark from living cork oak trees -high density fibreboard core treated with Jointguard moisture protection and Microban
	<b>HARMFUL ADDITIVES</b>	-Naturally hypo-allergenic, anti-microbial and anti-fungal - Cork Binder Resin formaldehyde-free polyurethane- non-toxic polymer suitable for food contact
	<b>HARMFUL EMISSIONS</b>	100% free of PVC's and absolutely no formaldehyde glue or binders
	<b>EMISSION STRENGTH OVER TIME</b>	n/a
	<b>TREATMENTS</b>	Polyurethane Floor Varnish - MP765 high-traffic water-base polyurethane system - Two-part catalyzed polyurethane for chemical and stain resistance, MP765 is a non-yellowing and transparent floor finish Tough and durable floor finish, A very low VOC content and water base means minimal odor during re-varnishing * MP765 is a fast-drying water-borne floor finish * Absolutely no residual odor or off-gassing
<b>MANUFACTURING</b>	<b>MANUFACTURING PROCESS</b>	Managed forests
	<b>HARMFUL EMISSIONS</b>	none
	<b>LOCATION OF MANUF. PLANT</b>	n/a
	<b>TESTS/CODES</b>	n/a
	<b>3<sup>RD</sup> PARTY CERTIFICATION</b>	USGBC, LEED, Forest Stewardship Council, National Wood Flooring Association
<b>INSTALLATION</b>	<b>INSTALLATION PROCEDURE</b>	Cork tile flooring is installed much as traditional vinyl or resilient flooring while our clic flooring is installed as a floating floor over existing floors or for speedy installation. Use ONLY 100% PORTLAND based patching compounds if subfloor patching is necessary. Duro-Design Contact Adhesive will be shipped with the tile. Provide clean, new short nap roller for utilization of Duro-Design contact adhesive or provide proper applicator for utilization of contact cement as recommended by Duro-Design.  Floating Cork Uniclic Flooring – according to manufacturers instructions – install 6 mil vapor barrier, taped at seams on entire floor – lay flooring in the direction/pattern as shown on drawings – allow 3/8 inch space for expansion.
	<b>INSTALLATION ADHESIVES</b>	DuroDesign
	<b>UNIT COST</b>	Varies
	<b>LIFE CYCLE ANALYSIS</b>	n/a
	<b>END OF SERVICE LIFE</b>	n/a
	<b>QUALITIES/PROPERTIES OF PRODUCT</b>	Durable, renewable
<b>MISC. PROPERTIES</b>	<b>MISC. COMMENTS</b>	
	<b>CONTRIBUTION TO LEED POINTS</b>	* MR Credit 4.1: Recycled Content: 10% (post-consumer + 1/2 pre-consumer) * MR Credit 4.2: Recycled Content: 20% (post-consumer + 1/2 pre-consumer) * MR Credit 6: Rapidly Renewable Materials. * IEQ Credit 4.1: Low-Emitting Materials: Adhesives and Sealants. * IEQ Credit 4.1: Low-Emitting Materials: Paints and Coatings. * ID Credit 1-1.4: Innovation in Design
<b>COMPANY PROFILE</b>	<b>GREEN PHILOSOPHY</b>	DuroDesign manufactures renewable and sustainable flooring, a low-VOC

<b><u>MAINTENANCE</u></b>		finishing system and low-VOC flooring adhesives as a continuing commitment to environmental design, sustainable building practices and beautiful green floors. Sustainable and managed harvests.
	<b>CONTACT</b>	(888) 528-8518 or (450) 978-3403 Fax (450) 978-2542 Email - info@durodesign.com Mailing Address DuroDesign Flooring, Inc. 4656 Louis B. Mayer St., Unit #9 Laval, QC H7P 6E4 CANADA
	<b>AFTER INSTALLATION</b>	Mop and water, vacuum