

<b>PRODUCT INFORMATION</b>	<b>TYPE OF PRODUCT</b>	Cork Flooring
	<b>COMPANY NAME</b>	Gerbert Limited
	<b>PRODUCT/COLLECTION NAME</b>	Dodge Cork Mediterranean Cork Verte Floating Floor
	<b>DESCRIPTION</b>	Clean and simple - one pattern available in a variety of finishes makes Dodge Cork a classic.  Cork floor tiles are produced from cork granules agglutinated with synthetic resins and baked under heat and pressure. The moisture content within the cork granules, the duration of the baking process, and the temperature used, controls the shading of cork tiles. Each production will yield a mixture of light, medium and dark colored tiles. The natural shading of cork tiles allows designers unlimited creativity.
<b>MATERIAL FEEDSTOCK</b>	<b>MATERIAL CONTENT</b>	Finish: Sanded (unfinished), Carnauba wax, poly-matte
	<b>RECYCLED CONTENT %</b>	78% total recycled content 78% preconsumer recycled content
	<b>RAPIDLY RENEWABLE CONTENT %</b>	n/a
	<b>HARMFUL ADDITIVES</b>	n/a
	<b>HARMFUL EMISSIONS</b>	n/a
	<b>EMISSION STRENGTH OVER TIME</b>	n/a
	<b>TREATMENTS</b>	Finish: Sanded (unfinished), Carnauba wax, poly-matte 4 types: unfinished, waxed, polyurethane satin, polyurethane gloss
<b>MANUFACTURING</b>	<b>MANUFACTURING PROCESS</b>	Not stated
	<b>HARMFUL EMISSIONS</b>	None stated
	<b>LOCATION OF MANUF. PLANT</b>	Manufactured in Portugal according to the requirements certified by DIN (Deutsches Institut for Normung-German Institute for Standards) and per Federal Standard LLL-431 b "Tile Cork"
	<b>TESTS/CODES</b>	None stated
	<b>3<sup>RD</sup> PARTY CERTIFICATION</b>	None stated
<b>INSTALLATION</b>	<b>INSTALLATION PROCEDURE</b>	Cork, being wood, will expand and shrink depending on temperature and humidity. Temperature and humidity at the installation site must be maintained at 68 degrees F and humidity must be controlled and kept below 65% and above 40% during the following time periods. To compensate for expansion and contraction of the floor covering and the building, which will occur due to seasonal changes, it is recommended to leave a 1/4" (6mm) span around the perimeter of the room.
	<b>INSTALLATION ADHESIVES</b>	Gerber Cork Cement
	<b>UNIT COST</b>	varies
	<b>LIFE CYCLE ANALYSIS</b>	n/a
	<b>END OF SERVICE LIFE</b>	n/a
<b>MISC. PROPERTIES</b>	<b>QUALITIES/PROPERTIES OF PRODUCT</b>	Superior acoustical rating Anti-static Shock absorbent Scuff resistant Renewable resource Sound absorbent
	<b>MISC. COMMENTS</b>	None stated
	<b>CONTRIBUTION TO LEED POINTS</b>	Maximum of 3 points – Credit numbers MR 4.1, 4.2, 6.0
<b>COMPANY PROFILE</b>	<b>GREEN PHILOSOPHY</b>	Cork is a readily renewable resource that qualifies for Leadership in Energy and Environmental Development credit and contributes to improved indoor air quality. Dodge Cork Tile is designed to meet stringent criteria required to earn points under the Materials and Resources and Indoor Environmental Quality Categories of LEED-NC and LEED-CI. Based on this criteria Dodge Cork products can assist architects and designers in obtaining up to 3 points toward LEED certification.
	<b>CONTACT</b>	Gerbert Limited 119 South Tree Drive Lancaster, Pennsylvania 17603-4944

		Phone: 800-828-9461 Fax: 717-394-1937 e-mail: <a href="mailto:gerbertinfo@gerbertltd.com">gerbertinfo@gerbertltd.com</a>
<b><u>MAINTENANCE</u></b>	<b>AFTER INSTALLATION</b>	Gentle vacuuming, polish floor using rotary buffing machine