

<b>PRODUCT INFORMATION</b>	<b>TYPE OF PRODUCT</b>	PVC-Free Flooring Tile
	<b>COMPANY NAME</b>	MoHawk
	<b>PRODUCT/COLLECTION NAME</b>	Stonewalk PVC-Free Flooring
	<b>DESCRIPTION</b>	The next generation of flooring, StoneWalk is the perfect blend of ecologically responsibility and performance. Made from naturally abundant resources, StoneWalk contains no PVC (polyvinyl chloride), halogens, or plasticizers and emits no VOC's into the environment. Much lighter than VCT, StoneWalk is easy to trim, resistant to handling damage, and dimensionally stable so installation is a breeze. Plus, StoneWalk is engineered to absorb sound, resist indentation and provides increased comfort underfoot while able to resist even light forklift traffic with out cracking.
<b>MATERIAL FEEDSTOCK</b>	<b>MATERIAL CONTENT</b>	ETHYLENE ACRYLIC Dolomite = 85% Other ingredients = 15%
	<b>RECYCLED CONTENT %</b>	45% Pre-consumer
	<b>RAPIDLY RENEWABLE CONTENT %</b>	None
	<b>HARMFUL ADDITIVES</b>	CRYSTALLINE SILICA (QUARTZ) NON-ASBESTOS TREMOLITE CARBON BLACK (in some colours)
	<b>HARMFUL EMISSIONS</b>	Solid material with different colours, characteristic odour.
	<b>EMISSION STRENGTH OVER TIME</b>	N/A
	<b>TREATMENTS</b>	N/A
<b>MANUFACTURING</b>	<b>MANUFACTURING PROCESS</b>	N/A
	<b>HARMFUL EMISSIONS</b>	N/A
	<b>LOCATION OF MANUF. PLANT</b>	CANAAN, CT
	<b>TESTS/CODES</b>	FloorScore Certified By SCS Certification Registration Number SCS-FS-01494
	<b>3<sup>RD</sup> PARTY CERTIFICATION</b>	FloorScore Certified By SCS Certification Registration Number SCS-FS-01494
<b>INSTALLATION</b>	<b>INSTALLATION PROCEDURE</b>	Mohawk Stonewalk Non-PVC Tiles must be installed in accordance with the manufacturers specifications, including sub flooring preparation and recommended adhesives. Complete product installation procedures, including sub flooring preparations and adhesive application are available in the Mohawk Stonewalk installation and floor preparation instructions.
	<b>INSTALLATION ADHESIVES</b>	Non-PVC Tile pressure sensitive adhesive This prduct contains no hazardous ingredients as defined by US Osha Hazard communication standard – 29 CFR 1910.1200 or section 13 of the Canadian Hazard Products Act
	<b>UNIT COST</b>	A
	<b>LIFE CYCLE ANALYSIS EXTRACTION</b>	N/A
	<b>END OF SERVICE LIFE</b>	N/A
<b>MISC. PROPERTIES</b>	<b>QUALITIES/PROPERTIES OF PRODUCT</b>	Because its tougher than VCT, Stonewalk can be used to bridge minor imperfections better than 1/8" VCT due to lower cold flow.
	<b>MISC. COMMENTS</b>	N/A
	<b>CONTRIBUTION TO LEED POINTS</b>	MR Credit 4.1 MR Credit 4.2 MR Credit 5.1 MR Credit 5.2 EQ Credit 3.2 EQ Credit 4.1 (SCAQMD Rile #1168)
<b>COMPANY PROFILE</b>	<b>GREEN PHILOSOPHY</b>	Being good stewards of our environment not only makes good business sense, it's the right thing to do. The Mohawk Group continues to drive environmentally sound practices and invest in the creation of life-enhancing, eco-friendly products and processes. Our goals are simple: engineer quality floor coverings that last longer, dramatically reduce energy use, evaluate preferable procurement, increase the use of recycled materials, and continue to improve our percentage of end-of-useful-life reclamation.

<b><u>MAINTENANCE</u></b>	<b>CONTACT</b>	name Keith Wall toll free 1-800-554-6637 ext: 36209 cell 704/458-0066 fax 704/344-0355 office 704/344-0655 email keith_wall@leescarpets.com
	<b>AFTER INSTALLATION</b>	Mohawk Stonewalk Non-PVC flooring requires simple regular cleaning and maintenance to retain the original appearance. For Further details on correct maintenance procedures, refer to Mohawk Stonewalk Maintenance Instructions.