

IAR Library: 09.64.00 Basket 2 2009  
Wood Flooring  
09.64.00  
2009

<b>PRODUCT INFORMATION</b>	<b>TYPE OF PRODUCT</b>	Hand-sraped Wood Flooring
	<b>COMPANY NAME</b>	EcoTimber
	<b>PRODUCT/COLLECTION NAME</b>	Hand-Scraped Hickory - Bourbon
	<b>DESCRIPTION</b>	<p>not "distressed" by machinery. Five-inch widths provide a truly rustic feel and an old-world appearance. Scratches and dings will not stand out as much as they sometimes do with smooth-surface flooring. The wood in these floors is 100% FSC Certified from well-managed forests, and made with a formaldehyde-free, zero-VOC adhesive.</p> <p>Thickness: 5/8"  Face Width: 3-5/8"  Length: 73-3/16"  Packaged in boxes containing 26.9 square feet</p>
<b>MATERIAL FEEDSTOCK</b>	<b>MATERIAL CONTENT</b>	<p>Satin sheen Aluminum-oxide enhanced UV-cured urethane finish  Scratch-resistant hardened acrylic top-coat  100% Bamboo  3-Ply Horizontal construction  Prefinished: Micro-beveled edges  Unfinished: Square edges</p>
	<b>RECYCLED CONTENT %</b>	N/A
	<b>RAPIDLY RENEWABLE CONTENT %</b>	100% Certified according to the Principles & Criteria of the Forest Stewardship Council (FSC), adhering to strict environmental and social standards
	<b>HARMFUL ADDITIVES</b>	N/A
	<b>HARMFUL EMISSIONS</b>	<p>Made with a formaldehyde-free adhesive that does not off-gas in the home.  Easily meets the E1 and 2012 CARB standards for indoor air quality</p>
	<b>EMISSION STRENGTH OVER TIME</b>	Made with a formaldehyde-free adhesive that does not off-gas in the home
	<b>TREATMENTS</b>	<p>Satin sheen Aluminum-oxide enhanced UV-cured urethane finish  Scratch-resistant hardened acrylic top-coat</p>
<b>MANUFACTURING</b>	<b>MANUFACTURING PROCESS</b>	N/A
	<b>HARMFUL EMISSIONS</b>	N/A
	<b>LOCATION OF MANUF. PLANT</b>	N/A
	<b>TESTS/CODES</b>	N/A
	<b>3<sup>RD</sup> PARTY CERTIFICATION</b>	<p>SFI (Sustainable Forestry Initiative)</p> <ul style="list-style-type: none"> <li>* Founded and dominated by the timber industry</li> <li>* Weak environmental protections</li> <li>* Allows conversion of natural forests (including old-growth) into tree farms</li> <li>* No mandatory Chain of Custody to keep out illegal wood</li> </ul> <p>CSA (Canadian Standards Association)</p> <ul style="list-style-type: none"> <li>* Allows conversion of natural forests (including old-growth) into tree farms</li> <li>* Fails to protect First Nations</li> </ul> <p>PEFC (Program for the Endorsement of Forest Certification)</p> <ul style="list-style-type: none"> <li>* Weak environmental standards</li> <li>* No mandatory Chain of Custody</li> <li>* Mutually recognizes virtually all forest certification systems, including SFI and CSA</li> <li>* PEFC wood could come from almost any source</li> </ul> <p>ISO (International Standards Organization)</p> <ul style="list-style-type: none"> <li>* Standards address manufacturing practices, not forest management</li> </ul> <p>IBAMA (Program of the Brazilian Government)</p>

		<ul style="list-style-type: none"> <li>* Low environmental standards, poorly enforced</li> <li>* No Chain of Custody</li> <li>* Many reports of corruption</li> </ul>
<b><u>INSTALLATION</u></b>	<b>INSTALLATION PROCEDURE</b>	Nail-down Glue-down (Recommended adhesive: EcoTimber HealthyBond-MS) Float (Recommended underlayment: EcoTimber Floating Floor Pad) Warranted over some radiant heat systems - please read installation instructions thoroughly
	<b>INSTALLATION ADHESIVES</b>	Recommended adhesive: EcoTimber HealthyBond-MS - EcoTimber HealthyBond Adhesive is solvent-free, isocyanate-free, has very little odor, negligible levels of VOCs (7 grams per liter), no hazardous chemicals -- and meets all federal, state and local indoor air quality regulations. It contains high solids for superior coverage (up to 240 square feet per 4-gallon pail) and is easy to spread with good early strength for an immediate "grab". HealthyBond is so strong, the only complaint we receive is that it's very difficult to pull up flooring that has been installed incorrectly.
	<b>UNIT COST</b>	A
	<b>LIFE CYCLE ANALYSIS EXTRACTION</b>	N/A
	<b>END OF SERVICE LIFE</b>	N/A
<b><u>MISC. PROPERTIES</u></b>	<b>QUALITIES/PROPERTIES OF PRODUCT</b>	A
	<b>MISC. COMMENTS</b>	N/A
	<b>CONTRIBUTION TO LEED POINTS</b>	MR 7 - Certified Wood EQ 4.4 - Low Emitting Materials - Composite Wood and Laminate Adhesives
<b><u>COMPANY PROFILE</u></b>	<b>GREEN PHILOSOPHY</b>	An EcoTimber floor is more than beautiful wood or bamboo. Since 1992, EcoTimber has been the only flooring company devoted exclusively to forest protection and indoor air quality. You can trust that an EcoTimber floor, no matter which one you choose, satisfies the highest environmental and health standards.
	<b>CONTACT</b>	5215 Central Avenue   Richmond CA 94804 t 510.809.8200   f 415.258.8455
<b><u>MAINTENANCE</u></b>	<b>AFTER INSTALLATION</b>	Use Proper Cleaning Products - To clean the EcoTimber factory urethane finish, we recommend the Bona-X® Swedish Formula Hardwood Floor Cleaner (www.bonakemi.com, 800-574-4674). Vinegar mixed with water (applied with a slightly damp mop – never wet-mop) is also effective at removing scuffs, dried spills, and dust film. To remove hard-to-clean substances such as chewing gum, use Goof-Off® or Goo-Gone®, available at most hardware stores and supermarkets. Floor waxes, oil soaps, and petroleum-based cleaners should not be used under any circumstances.