

PRODUCT INFORMATION	TYPE OF PRODUCT	Rubber Tile
	COMPANY NAME	Roppe
	PRODUCT/COLLECTION NAME	Spike skate
	DESCRIPTION	Use it anywhere damage from skates, spikes or cleats is a concern. Its strength and durability make it perfect for ice areas, locker room entrances and exits and players' walk ways to sports fields and ball parks.
MATERIAL FEEDSTOCK	MATERIAL CONTENT	Made of 9mm solid rubber with a textured design profile that resist scuffs, gouges, cuts, cigarette burns, and most chemicals and common substances.
	RECYCLED CONTENT %	Varies by color
	RAPIDLY RENEWABLE CONTENT %	Varies by color and recycled content
	HARMFUL ADDITIVES	None
	HARMFUL EMISSIONS	None
	EMISSION STRENGTH OVER TIME	None
	TREATMENTS	N/A
MANUFACTURING	MANUFACTURING PROCESS	Roppe's Spike/Skate Resistant flooring not manufactured with an installation directional logo, and must be installed in the same direction as packaged in the original box. Always dry-lay each floor before beginning to ensure the desired look is achieved, while checking for turned or shaded tile. Notice: It is the Flooring Installer's direct responsibility to inspect and loose lay the flooring in the room or area prior to installation to determine the proper layout and best overall appearance. Flooring Installer must inspect all material for manufacturing imperfections and irregularities prior to installation. All manufacturing imperfections or irregularities must be reported to the appropriate authority. The use of skate/cleat guards is recommended to prevent damage to the flooring. Roppe Spike/Skate Resistant Rubber Tile must be installed using either ROP435 Solvent Free Epoxy Flooring Adhesive (excluding metal and flexing substrates) or ROP535U "Universal" Two-Component Urethane Enhanced Epoxy Adhesive each limited to specific applications and substrate types. The ROP435 Free Epoxy Flooring Adhesive or ROP535U "Universal" Two-Component Urethane Enhanced Epoxy Adhesive must be used for installations in areas where the flooring will be subjected to lateral shear stresses and/or rolling loads, depending on substrate type. Spike/Skate Resistant Rubber Tile must be installed in accordance with Roppe's recommendations in order for the product warranty to be in effect.
	HARMFUL EMISSIONS	Most of our products meet CHPS criteria and are FLOORSCORE certified, which means they release little if any harmful emissions.
	LOCATION OF MANUF. PLANT	Ohio
	TESTS/CODES	N/A
	3RD PARTY CERTIFICATION	LEED: MR4.1, MR4.2, MR5.1, MR5.2 and MR6. CHPS Certification Floor Score
INSTALLATION	INSTALLATION PROCEDURE	Install with manufacturer's own adhesive closely following manufactures' instructions at www.roppe.com
	INSTALLATION ADHESIVES	6.3.1 ROP 435 Solvent Free Epoxy Flooring Adhesive: ROP 435 Solvent Free Epoxy Flooring Adhesive is a solvent free, non-flammable, high performance epoxy adhesive for indoor installations over porous and non-porous substrates (excluding metal or slightly flexing substrates) on grade, below grade, or above grade. The ROP435 Solvent Free Epoxy Flooring Adhesive must be used for installations in areas where the flooring will be subjected to lateral shear stresses and/or rolling loads, and most other non-porous substrates, excluding metal and other slightly flexing substrates.
	UNIT COST	This is the most expensive and durable surface regarding length of life cycle and minimal maintenance, all 6 colors are available at a single price point.
	LIFE CYCLE ANALYSIS EXTRACTION	N/A
	END OF SERVICE LIFE	Return to Roppe for recycling with Impact program, which is not limited to

		Roppe products, the only stipulation is it must be Type TS (vulcanized, thermoset rubber). What this translates into is that in a little more than a year's time, we have been able to divert 1,955 tons from the landfills.
MISC. PROPERTIES	QUALITIES/PROPERTIES OF PRODUCT	Excellent wear resistance for high traffic areas
	MISC. COMMENTS	Shipping: Shrink wrapped and palletized
	CONTRIBUTION TO LEED POINTS	MR2, MR4.1, MR4.2, MR5.1, and MR5.2
COMPANY PROFILE	GREEN PHILOSOPHY	At Roppe, we've consciously decided to be part of the solution. That means we're not just committed to making better products – we're dedicated to making a positive impact on the environment as well. Our "green" products meet high environmental standards and may contribute to the U.S. Green Building Council's LEED® Green Building Certification System. From tiles and treads to wall base and adhesives, our EcoEffects® products meet high environmental standards without compromising color selection, performance, durability or style.
	CONTACT	Roppe Corporation 1602 N. Union Street P.O. Box 1158 Fostoria, Ohio USA 44830-1158 Phone: 419.435.8546 Toll Free: 800.537.9527 Fax: 419.435.1056 Email: sales@roppe.com Web Site: www.roppe.com
MAINTENANCE	AFTER INSTALLATION	www.roppe.com