

IAR Library:
09.65.19 RO5 2012
Flooring
09.65.19
2012

PRODUCT INFORMATION	TYPE OF PRODUCT	Rubber Tile
	COMPANY NAME	Roppe
	PRODUCT/COLLECTION NAME	Metal tread
	DESCRIPTION	Constructed of heat-treated exterior-grade aluminum 6063T3 with an epoxy filed face that increases slip resistance and is resistant to marring, scratching and chipping.
MATERIAL FEEDSTOCK	MATERIAL CONTENT	Stocked in 9" nominal depths and 36" and 48" lengths. Nominal 7-1/2" and 11" depths available by special order.
	RECYCLED CONTENT %	Varies by color
	RAPIDLY RENEWABLE CONTENT %	Varies by color and recycled content
	HARMFUL ADDITIVES	None
	HARMFUL EMISSIONS	None
	EMISSION STRENGTH OVER TIME	None
	TREATMENTS	N/A
MANUFACTURING	MANUFACTURING PROCESS	Roppe Rubber Stair Treads are vulcanized and constructed of specially formed, compression molded, high-grade synthetic rubber compound with stabilizing fillers and color pigments, extenders and process oils. These treads are manufactured with added thickness in high-wear areas to ensure long life. Roppe Rubber Stair Treads are PVC Free and fully conform to ASTM F-2169, Type TS. Safety abrasive strips and custom strips can be added for extra traction or to aid the visually impaired. The Stair Treads are also available with self-illuminating photoluminescent abrasive glow strips for added safety in darkened conditions.
	HARMFUL EMISSIONS	Most of our products meet CHPS criteria and are FLOORSCORE certified, which means they release little if any harmful emissions.
	LOCATION OF MANUF. PLANT	Ohio
	TESTS/CODES	N/A
	3RD PARTY CERTIFICATION	LEED: MR4.1, MR4.2, MR5.1, MR5.2 and MR6. CHPS Certification Floor Score
INSTALLATION	INSTALLATION PROCEDURE	Install with manufacturer's own adhesive closely following manufactures' instructions at www.roppe.com
	INSTALLATION ADHESIVES	6.3.1 ROP360 Acrylic Tile and Stair Tread Adhesive: ROP360 Acrylic Tile and Stair Tread Adhesive is a solvent free, high strength, acrylic adhesive for indoor installations over recommended and properly prepared concrete and wood subfloors only, on grade or above grade. Use of this adhesive is limited to casual foot traffic, in areas where there are no lateral shear stresses or rolling loads, nor in areas that will not be subjected to topical moisture or liquids.
	UNIT COST	All colors are available at a single price point.
	LIFE CYCLE ANALYSIS EXTRACTION	N/A
	END OF SERVICE LIFE	Return to Roppe for recycling with Impact program, which is not limited to Roppe products, the only stipulation is it must be Type TS (vulcanized, thermoset rubber). What this translates into is that in a little more than a year's time, we have been able to divert 1,955 tons from the landfills.
	MISC. PROPERTIES	Custom color matching is available and ideal to show off school or corporate branding colors.
MISC. PROPERTIES	QUALITIES/PROPERTIES OF PRODUCT	Custom color matching is available and ideal to show off school or corporate branding colors.
	MISC. COMMENTS	Shipping: Shrink wrapped and palletized
	CONTRIBUTION TO LEED POINTS	MR2, MR4.1, MR4.2, MR5.1, and MR5.2
COMPANY PROFILE	GREEN PHILOSOPHY	At Roppe, we've consciously decided to be part of the solution. That means we're not just committed to making better products – we're dedicated to making a positive impact on the environment as well. Our "green" products meet high environmental standards and may contribute to the U.S. Green Building Council's LEED® Green Building Certification System. From tiles and treads to wall base and adhesives, our EcoEffects® products meet high environmental standards without compromising color selection, performance, durability or style.

	CONTACT	Roppe Corporation 1602 N. Union Street P.O. Box 1158 Fostoria, Ohio USA 44830-1158 Phone: 419.435.8546 Toll Free: 800.537.9527 Fax: 419.435.1056 Email: sales@roppe.com Web Site: www.roppe.com
<u>MAINTENANCE</u>	AFTER INSTALLATION	www.roppe.com