

PRODUCT INFORMATION	TYPE OF PRODUCT	Rubber Tile- Wall base/Floor base
	COMPANY NAME	Roppe
	PRODUCT/COLLECTION NAME	Pinnacle
	DESCRIPTION	Pinnacle is the professional's choice because this 100% type TS vulcanized rubber base is highly durable and extremely flexible, allowing for easy installation around columns, corners and architectural curves.
MATERIAL FEEDSTOCK	MATERIAL CONTENT	100% synthetic rubber blended with stabilizing fillers, color pigments, and processing oils.
	RECYCLED CONTENT %	None
	RAPIDLY RENEWABLE CONTENT %	10% natural rubber
	HARMFUL ADDITIVES	None
	HARMFUL EMISSIONS	None
	EMISSION STRENGTH OVER TIME	None
	TREATMENTS	N/A
MANUFACTURING	MANUFACTURING PROCESS	We produce mainly SBR rubber products, we use heat, steam and pressure to vulcanize the rubber into different forms – wall base, tile or stair treads. We are careful to run our lines in as efficient manners as possible, which includes initiatives such as running higher use lines during off peak hours and recycling our water for the steam function. Our main waste management strategy is to eliminate the waste from the cycle. However, since that is not always possible, we have implemented a zero landfill policy. We utilize the same IMPACT program that is offered to customers within our own manufacturing processes and it has been quite successful in minimizing, and almost eliminating the landfill option that was heavily relied here for many years. I would also add that our small community does not offer a public recycling program, but our employees are encouraged to recycle their plastics, newspapers, magazines and aluminum cans here at Roppe. The monies earned from this effort are put into a fund on an annual basis and divided between all of the employee's college students. This has been a very lucrative fundraiser for our kids who earn at least \$1000 per student each summer for the next school year.
	HARMFUL EMISSIONS	Most of our products meet CHPS criteria and are FLOORSCORE certified, which means they release little if any harmful emissions.
	LOCATION OF MANUF. PLANT	Ohio
	TESTS/CODES	Meets ADA recommendations of COF for ramps and flat surfaces.
	3RD PARTY CERTIFICATION	LEED: MR4.1, MR4.2, MR5.1, MR5.2 and MR6. CHPS Certification FloorScore
INSTALLATION	INSTALLATION PROCEDURE	Install with manufacturer's own adhesive closely following manufacture's instructions
	INSTALLATION ADHESIVES	Varies according to substrate
	UNIT COST	A
	LIFE CYCLE ANALYSIS EXTRACTION	N/A
	END OF SERVICE LIFE	Return to Roppe for recycling with Impact program, which is not limited to Roppe products, the only stipulation is it must be Type TS (vulcanized, thermoset rubber). What this translates into is that in a little more than a year's time, we have been able to divert 1,955 tons from the landfills.
MISC. PROPERTIES	QUALITIES/PROPERTIES OF PRODUCT	Available in 7 profiles: Slate Design, Low Profile Raised Design, Textured Design, Raised Square Design, Raised Circular Vantage Profile, Hammered and Warning Tile Design. Designed for high durability and ease of maintenance throughout the product life cycle. Roppe Spike/Skate Resistant Rubber Tile is not to be used in commercial kitchens or in areas exposed to animal fats, greases, oils, solvents, strong detergents, or where there is excessive topical moisture.
	MISC. COMMENTS	Shipping: Shrink wrapped and palletized
	CONTRIBUTION TO LEED POINTS	MR2, MR4.1, MR4.2, MR5.1, and MR5.2
COMPANY PROFILE	GREEN PHILOSOPHY	At Roppe, we've consciously decided to be part of the solution.

<u>MAINTENANCE</u>		That means we're not just committed to making better products – we're dedicated to making a positive impact on the environment as well. Our "green" products meet high environmental standards and may contribute to the U.S. Green Building Council's LEED® Green Building Certification System. From tiles and treads to wall base and adhesives, our EcoEffects® products meet high environmental standards without compromising color selection, performance, durability or style.
	CONTACT	Roppe Corporation 1602 N. Union Street P.O. Box 1158 Fostoria, Ohio USA 44830-1158 Phone: 419.435.8546 Toll Free: 800.537.9527 Fax: 419.435.1056 Email: sales@roppe.com Web Site: www.roppe.com
	AFTER INSTALLATION	Mop regularly and buff/polish occasionally using recommended products based on your sealant/finish selection