PRODUCT	TYPE OF PRODUCT	Wall covering
INFORMATION	TIPE OF PRODUCT	waii covering
	COMPANY NAME	Roos Wallcovering also sold by Sherwin Williams distr.
	PRODUCT/COLLECTION NAME	Envision
	DESCRIPTION	The EnVision® Portfolio collection was inspired by the need for a new
		generation of wallcovering that is a PVC Free alternative to traditional
		vinyl. The collection appeals to all markets from hospitality to healthcare
		and even commercial offices to retail store design
MATERIAL FEEDSTOCK	MATERIAL CONTENT	Breathable, natural fibrous polyester cellulose non-woven:
	DEOVOLED CONTENT 0/	Nonwoven/Cellulose Polyester & Acrylic
	RECYCLED CONTENT % RAPIDLY RENEWABLE CONTENT	Contains recycled and renewable content
	RAPIDLY RENEWABLE CONTENT	n/a
	HARMFUL ADDITIVES	• PVC-free
	TIANIMI GE ABBITIVES	No heavy metals
		• No VOC's
		Printed with water based inks
		No harmful substances
	HARMFUL EMISSIONS	Low VOC emissions.
	EMISSION STRENGTH OVER TIME	n/a
	TREATMENTS	n/a
MANUEACTURING	MANUE A CTURING PROCESS	
MANUFACTURING	MANUFACTURING PROCESS HARMFUL EMISSIONS	n/a Low VOC emissions.
	LOCATION OF MANUF. PLANT	n/a
	TESTS/CODES	Type II and Type III, Category V of ASTM F793-98, Class A ASTM-E84-
	TESTS/CODES	01 or E84-98
	3 RD PARTY CERTIFICATION	Listed in Greenspec
INSTALLATION	INSTALLATION PROCEDURE	All wallcoverings must be installed by an experienced commercial
		wallcovering installation professional who understands wallcovering use
		and installation requirements, including the requirement to test for and
		eliminate sources of moisture prior to the installation of wallcovering. •
	INCTALLATION ADJECTIVES	Low waste factor during installation Primer and Adhesive: Recommend Zinsser Vapor Permeable System -
	INSTALLATION ADHESIVES	Can be either dry hung or pulled thrugh the pasting machine -
		Dimensionally stable (minimal shrinkage) - Easy to remove (can be dry
		stripped)
	UNIT COST	See representative.
	LIFE CYCLE ANALYSIS	Superior life cycle performance with minimal maintenance. Breathable for
	EXTRACTION	longer life span. ASTM D 2486 300 cycles.
14100 00000000000	END OF SERVICE LIFE	100% recyclable, Easy to remove (can be dry stripped)
MISC. PROPERTIES	QUALITIES/PROPERTIES OF PRODUCT	Breathable, eco-friendly, recyclable, and long-life cycle.
	MISC. COMMENTS	Can be either dry hung or pulled thrugh the pasting machine -
	WIIGO: GOWINIEITIG	Dimensionally stable (minimal shrinkage)
	CONTRIBUTION TO LEED POINTS	Energy & Atmosphere:
		Optimize Energy Performance 1-3
		Materials & Resources:
		Sustainable Purchasing 1-5
		Building Reuse 1-2
		Recycled Content 1-2 Solid Waste Mgmt., Durable 1
		Certified Wood 1
		Environmental Quality:
		Low-Emitting Adhesives 1
		Innovation & Design:
		Innovation in Design 1-4
COMPANY PROFILE	GREEN PHILOSOPHY	Roos International has been pioneering environmentally responsible
		wallcoverings since before "green" was fashionable. Through these
		innovations, we have set a new standard for sustainable wallcoverings
		that promotes a healthy building environment to maximize occupant productivity and minimize environmental impact. Our eco friendly
		wallcoverings are PVC free, contain recycled content and are made from
I		1 manustratings are 1 to 1100, contain recycled content and are made 110111

		rapidly renewable resources.
	CONTACT	Roos Int. 1020 N.W. 6 th St Suite H
		Deerfield Beech, FL 33442
		www.roosintl.com
		support@roosintl.com
		1-800-888-2776
MAINTENANCE	AFTER INSTALLATION	Mild soap and water maintenance.