

PRODUCT INFORMATION	TYPE OF PRODUCT	Wall covering	
	COMPANY NAME	Eykon	
	PRODUCT/COLLECTION NAME	Source One	
	DESCRIPTION	Textile Wallcovering	
MATERIAL FEEDSTOCK	MATERIAL CONTENT	Rayon facing, paper backing Polyester/viscose facing, paper backing Silk facing, paper backing Linen facing, paper backing Linen or Linen/cotton combination facing, paper backing Silk or silk/cotton combination facing, paper backing Polyester/viscose/linen/cotton facing, paper backing Linen/viscose facing, paper backing Polyester/viscose/cotton/polypropylene facing, paper backing Cotton/viscose/polyester facing, paper backing Polyester/viscose/polyamide facing, paper backing Cotton/viscose/polyamide facing, paper backing	
	RECYCLED CONTENT %	Varies with styles. Some styles include recycled paper backing that is 35% of the total product weight.	
	RAPIDLY RENEWABLE CONTENT %	Annually renewable content: Silk and linen	
	HARMFUL ADDITIVES	Some styles are made with water-based inks and coatings.	
	HARMFUL EMISSIONS	Some styles state that no ozone-depleting chemicals have been used.	
	EMISSION STRENGTH OVER TIME	N/A	
	TREATMENTS	Some are treated with a Teflon coating for stain resistance. Some are treated with a water-repellent top finish. These treatments have no sustainability information provided.	
	MANUFACTURING	MANUFACTURING PROCESS	N/A
		HARMFUL EMISSIONS	N/A
LOCATION OF MANUF. PLANT		The materials manufactured locally in Memphis, TN	
TESTS/CODES		ASTM-E 84	
3RD PARTY CERTIFICATION		N/A	
INSTALLATION	INSTALLATION PROCEDURE	http://eykon.net/Install_Wallcovering.aspx	
	INSTALLATION ADHESIVES	Use a commercial grade pre-mixed adhesive. A temperature above 55F should be maintained in both areas of installation and storage.	
	UNIT COST	Varies by size	
	LIFE CYCLE ANALYSIS EXTRACTION	N/A	
	END OF SERVICE LIFE	Some styles are biodegradable.	
MISC. PROPERTIES	QUALITIES/PROPERTIES OF PRODUCT	Natural fibers offer distinctive style.	
	MISC. COMMENTS	Request a "cutting for approval" sample prior to order.	
	CONTRIBUTION TO LEED POINTS	MR 4, 5 and MR 6 depending upon style	
COMPANY PROFILE	GREEN PHILOSOPHY	Source One believes in conserving our planet for future generations.	
	CONTACT	5675 East Shelby Drive Memphis, TN 38141 Phone: 901-365-1903 Toll Free: 800-222-7866 Fax: 901-366-0447 e-mail: info@eykon.net	
MAINTENANCE	AFTER INSTALLATION	Use traditional cleaning methods: washing, wiping, vacuuming. Always refer to the manufacturer's guidelines when cleaning wallcoverings. Stains should be removed as soon as possible to eliminate any reaction between the stain and the wallcovering, and to prevent permanent discoloration. Ordinary dirt spots can be removed with a mild soap and warm water. Rinse thoroughly with clean water. Blot dry with a soft lint-free towel. For difficult stains that are surface deep, use of a stronger detergent is recommended. Try an inconspicuous spot first, before attempting an entire wall. Always rinse after applying a detergent.	

		<p>Abrasive rubbing of spots should be avoided. Do not use steel wool, powdered cleaners, or active solvent-type preparations, such as nail polish remover, tar and bug removers, etc. as they may damage the wallcovering. Textile wallcoverings are decorative and require care in cleaning. Occasional vacuuming will remove most of the dirt and lint, and maintain the product's fresh look and appearance</p>
--	--	---