

<b>PRODUCT INFORMATION</b>	<b>TYPE OF PRODUCT</b>	Wall coverings
	<b>COMPANY NAME</b>	Innovations
	<b>PRODUCT/COLLECTION NAME</b>	Specialty Wallcoverings
	<b>DESCRIPTION</b>	Unique in color, pattern and texture
<b>MATERIAL FEEDSTOCK</b>	<b>MATERIAL CONTENT</b>	The primary composition for all Innvironments Type II products is wood pulp from managed forests and recyclable fabric fibers
	<b>RECYCLED CONTENT %</b>	Varies per item
	<b>RAPIDLY RENEWABLE CONTENT %</b>	Non-vinyl Type II wallcovering that is a bio-degradable composition of soy, corn and potatoes that form a non-chemical plastic film over a backing made from recycled paper and kanaf, a rapidly renewable resource similar to bamboo made from rapidly renewable or recycled content.
	<b>HARMFUL ADDITIVES</b>	PVC and plasticizer free and use water based inks and minerals to achieve color and sheen
	<b>HARMFUL EMISSIONS</b>	Manufactured from non-toxic materials to eliminate indoor air quality issues.
	<b>EMISSION STRENGTH OVER TIME</b>	manufactured with non-toxic inks and are PVC-free, to reduce the negative health effects of off-gassing
	<b>TREATMENTS</b>	low-VOC
<b>MANUFACTURING</b>	<b>MANUFACTURING PROCESS</b>	Innovations employs LEED accredited professionals to ensure the adherence to the most up-to-date LEED requirements and manufacturing processes
	<b>HARMFUL EMISSIONS</b>	PVC-free, non-toxic, low-VOC, and made from rapidly renewable or recycled content
	<b>LOCATION OF MANUF. PLANT</b>	150 Varick St., New York, NY 10013
	<b>TESTS/CODES</b>	Meet or exceeded all Federal Standard CCC-W-408-D tests including: washability, scrubbability, abrasion resistance, stain resistance, smoke development and flame spread
	<b>3<sup>RD</sup> PARTY CERTIFICATION</b>	Qualifies for credits in the US Green Building Council (USGBC), Leadership in Energy and Environmental Design (LEED) Rating System
<b>INSTALLATION</b>	<b>INSTALLATION PROCEDURE</b>	<p><b>HANGING/CLEANING INSTRUCTIONS FOR NAUTILUS/AEGEAN</b></p> <p><b>Important Notice</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Imported natural wallcoverings such as NAUTILUS is handcrafted from natural materials.</li> <li><input type="checkbox"/> NAUTILUS is delicate, exercise care in handling to avoid damage. No adjustment or claim will be considered because of variation in color or shading once material has been cut. Flaking or lifting of the mica fiber can be expected as it is inherent in the pattern.</li> <li><input type="checkbox"/> There are often slight irregularities in the natural material and coloration.</li> <li><input type="checkbox"/> Seams may be obvious upon installation and there will be a panel effect. This variation is the natural characteristic of these wallcoverings and it is not considered a defect.</li> <li><input type="checkbox"/> All rolls must have the same production number. Hang in sequence as cut from bolt starting with the highest first.</li> <li><input type="checkbox"/> These products must be handled with care!</li> </ul> <p><b>Prior to Installation</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Carefully inspect the installation after applying three strips before proceeding. If, at any time during the installation, a discrepancy occurs, stop. Contact the designer or Innovations before proceeding.</li> <li><input type="checkbox"/> Avoid folding or creasing which may create markings or damage on the product.</li> <li><input type="checkbox"/> Material has a factory edge and must be trimmed.</li> </ul> <p><b>Wall Preparation</b></p> <ul style="list-style-type: none"> <li><input type="checkbox"/> Proper wall preparation is essential. Walls must be smooth and clean, wallcoverings will not adhere to dirt, soap or grease. Clean the walls with household detergent or ammonia and rinse with clean water.</li> </ul>

		<input type="checkbox"/> If working around switch-plates turn off electricity. <input type="checkbox"/> Remove any loose or flaking paint and fill cracks with packing compound. <input type="checkbox"/> Sand to a smooth finish. Sand off bumps. <input type="checkbox"/> Apply a single coat of pigmented sealer on new and unpainted walls, followed by a coat of wallcovering size/primer like Roman R35. <b>Important Notes for Application</b> <input type="checkbox"/> A heavy-duty clear adhesive should be used, read the label. Apply paste with roller to ensure even application taking care not to get adhesive on surface. Do not use a pasting machine. Booking time should fall between 5-10 minutes. Paste and hang one strip at a time. Avoid washing material with water completely. Treat your product with extreme care. <input type="checkbox"/> Material should be STRAIGHT HUNG. <input type="checkbox"/> Material should be table trimmed and butted at the seam. <input type="checkbox"/> Use a soft bristle brush to apply wallcovering to wall. Do not use a metal knife or stiff sweep. Use extreme care at seams and face as not to damage surface of natural wallcovering! <b>Cleaning Instructions</b> No adhesive must come in contact with the face of this material. If cleaning is necessary, avoid rubbing. Completely avoid washing material with water. <input type="checkbox"/> Do not paste more than 3 strips. Carefully inspect the installation after applying three strips before proceeding. If, at any time during the installation, a discrepancy occurs, stop. Contact the designer or Innovations before proceeding. <b>DO NOT USE A PASTING MACHINE WITH THIS WALLCOVERING</b>
	<b>INSTALLATION ADHESIVES</b>	Not specified
	<b>UNIT COST</b>	Varies per item
	<b>LIFE CYCLE ANALYSIS EXTRACTION</b>	Not specified
	<b>END OF SERVICE LIFE</b>	30% of material is recyclable
<b>MISC. PROPERTIES</b>	<b>QUALITIES/PROPERTIES OF PRODUCT</b>	All of the wallcoverings in the Innvironments line are breathable, thus aid in the reduction of mold and mildew, a component in Sick Building Syndrome. These wallcoverings are excellent for hot and humid locations, as they do not create a vapor barrier if installed correctly
	<b>MISC. COMMENTS</b>	n/a
	<b>CONTRIBUTION TO LEED POINTS</b>	Contributes to LEED credits
<b>COMPANY PROFILE</b>	<b>GREEN PHILOSOPHY</b>	We are committed to creating products that are not only breathable and sustainable, but also stylish and durable
	<b>CONTACT</b>	Tel: 800.227.8053 Email: njsample@innovationsusa.com
<b>MAINTENANCE</b>	<b>AFTER INSTALLATION</b>	Remove ordinary dirt and smudges with a mild soap and warm water solution. Rinse with clean, clear water. Dry with a soft, lint free cloth or towel. Do not scrub with a nylon brush or abrasive cleaner.