

PRODUCT INFORMATION	TYPE OF PRODUCT	Wall covering
	COMPANY NAME	Eykon Wallcovering
	PRODUCT/COLLECTION NAME	Scion
	DESCRIPTION	Breathable, non-pvc wallcovering
MATERIAL FEEDSTOCK	MATERIAL CONTENT	ECORE Advanced Wall Technology- polyester and co-polyester microfilament fiber.
	RECYCLED CONTENT %	n/a
	RAPIDLY RENEWABLE CONTENT %	n/a
	HARMFUL ADDITIVES	Non-PVC substrate. Printed with water-based inks. <ul style="list-style-type: none"> • Does not contain Perfluoro Octanoic Acid (PFOA), nor will it degrade to PFOA. • Does not contain formaldehyde. • Cadmium- and mercury-free. • Low energy manufacturing with innovative water recycling process.
	HARMFUL EMISSIONS	Greenguard for low VOC- see below
	EMISSION STRENGTH OVER TIME	n/a
	TREATMENTS	Protective stain resistant top coating.
MANUFACTURING	MANUFACTURING PROCESS	ECORE technology is based on a revolutionary construction that uses nano-structures to create an innovative, lightweight, non-PVC substrate.
	HARMFUL EMISSIONS	GREENGUARD Indoor Air Quality Certified® for its low VOC emissions. GREENGUARD Children & Schools Certified SM for its very low emissions
	LOCATION OF MANUF. PLANT	Columbus, MS
	TESTS/CODES	ASTM E-96 Method B, Meets or exceeds Class A wallcovering requirements, NFPA 101 and IBC Class A Interior wall and finish rating when tested using ASTM-E84 method on Type X gypsum board and when tested in accordance with NFPA 286, and MEA Approved, NY Department of Buildings.
	3RD PARTY CERTIFICATION	GreenGuard
INSTALLATION	INSTALLATION PROCEDURE	All wallcoverings must be installed by an experienced commercial wallcovering installation professional who understands wallcovering use and installation requirements, including the requirement to test for and eliminate sources of moisture prior to the installation of wallcovering.
	INSTALLATION ADHESIVES	Use heavy-duty, clear-based adhesive. All adhesives must contain a mold inhibitor.
	UNIT COST	See representative.
	LIFE CYCLE ANALYSIS EXTRACTION	Superior life cycle performance with minimal maintenance. Breathable for longer life span. ASTM D 2486 300 cycles.
	END OF SERVICE LIFE	Commercial wallcoverings featuring Ecore are 100% post-consumer recyclable. Construction waste as well as post-use material can be returned for recycling as part of the Ecore Reclamation Program.
MISC. PROPERTIES	QUALITIES/PROPERTIES OF PRODUCT	Breathable, eco-friendly, recyclable, and long-life cycle.
	MISC. COMMENTS	ALL Ecore WALLCOVERINGS REQUIRE A TINTED PRIMER CONTAINING A MOLD INHIBITOR.
	CONTRIBUTION TO LEED POINTS	Category: Materials & Resources: MR 5.1: Regional Material: 1 20% manufactured locally - for projects within a 500 mile radius of Columbus, MS (see right). MR 2.1: Construction Waste Management/ Divert 50% from landfill.2 MR 2.2: Construction Waste Management/ Divert 75% from landfill.3 Category: Environmental Quality: EQ 4.1: Low Emitting Materials: Adhesives and Sealants.4
COMPANY PROFILE	GREEN PHILOSOPHY	With the new century came the conversion to Eykon and a new mission statement (see below). We have developed environmentally friendly products as well as recycled & recyclable products. Many items are available with microvent which makes them breathable. Eykon is dedicated to developing and marketing interior finish products focused on satisfying our customer's needs. Our products provide solutions for problems utilizing creative design, color correctness, and futuristic construction. Our products are delivered to market via professionals who

<u>MAINTENANCE</u>	CONTACT	<p>provide information, service, and quality at the highest level possible.</p> <p>OMNOVA Solutions Fairlawn, OH 44333 www.omnova.com Eykon Wallcovering Source Tommy Kerr 5675 E. Shelby Dr. Memphis, TN 38141 336.202.1056 cell</p>
	AFTER INSTALLATION	<p>For best performance, stains should be blotted and removed as soon as possible to limit any reaction between the staining agent and wallcovering. Ordinary dirt and smudges. A clean, damp sponge with warm water will remove many common smudges and dirt. If the damp sponge fails to clean dirt and smudges, follow instructions for other stains. Do not use harsh cleaning materials, solvents; steel wool abrasive cleaners or methods that could damage wall coverings. Five-year warranty.</p>