	I =	Lev.
PRODUCT	TYPE OF PRODUCT	Finishes
<u>INFORMATION</u>	COMPANY NAME	A
	PRODUCT/COLLECTION NAME	Anzea Deli-Frieze
MATERIAL FEEDOTOOK	DESCRIPTION	Finish: Graffiti-Free
MATERIAL FEEDSTOCK	MATERIAL CONTENT RECYCLED CONTENT %	100% Wool Face (38% Wool/62% Cotton) NA
	RAPIDLY RENEWABLE CONTENT	NA NA
	%	IVA
	HARMFUL ADDITIVES	NA
	HARMFUL EMISSIONS	None
	EMISSION STRENGTH OVER TIME	None
	TREATMENTS	NA
MANUFACTURING	MANUFACTURING PROCESS	NA
	HARMFUL EMISSIONS	None
	LOCATION OF MANUF. PLANT	Germany
	TESTS/CODES	Flammability:
		CAL 117, NFPA 260
		Upholstery
		California Technical Bulletin #117 Section E - Class 1 (Pass)
		Direct Glue Wall coverings and Adhered Panels
		ASTM E 84 (Adhered Mounting Method) - Class A or Class 1
		Wrapped Panels and Upholstered Walls
		Whapped I allels and Opholstered Walls
		ASTM E 84 (Unadhered Mounting Method) - Class A or Class 1
		Drapery
		NFPA 701- Pass
	3 RD PARTY CERTIFICATION	NA NA
INSTALLATION	INSTALLATION PROCEDURE	NA NA
	INSTALLATION ADHESIVES	NA
	UNIT COST	\$12/yd
	LIFE CYCLE ANALYSIS	The product is energy efficient
	EXTRACTION	Leatiful area Freezada 100 000 darrible with (in manhaeli)
MICC DEODERTIES	END OF SERVICE LIFE	Last for ever; Exceeds 100,000 double rubs (wyzenbeek)
MISC. PROPERTIES	QUALITIES/PROPERTIES OF PRODUCT	NA
	MISC. COMMENTS	Width: 54"
		Repeat: None
		Weight: 21.94 oz/linear yard
	CONTRIBUTION TO LEED POINTS	NA NA
	-	NA
COMPANY PROFILE	GREEN PHILOSOPHY	
	CONTACT	901 Foch Street
		Fort Worth, TX 76107
		Phone: 817.336.2310
		Fax: 817.336.9548
MAINTENANCE	AFTER INICTALL ATION	Email: customerservice@anzea.com
	AFTER INSTALLATION	S (solvent or dry cleaning products): To prevent overall soiling, frequent vacuuming or light brushing to remove dust and grime is recommended.
		Spot clean using a mild water-free solvent or dry cleaning product. Clean
		only in a well-ventilated room and avoid any product containing carbon
		tetrachloride, which is highly toxic. Pretest a small area before
		proceeding.
	•	