

PRODUCT INFORMATION	TYPE OF PRODUCT	Finishes
	COMPANY NAME	Anzea
	PRODUCT/COLLECTION NAME	Faux Maux
	DESCRIPTION	Finish: Graffiti-Free
MATERIAL FEEDSTOCK	MATERIAL CONTENT	100% Polyester
	RECYCLED CONTENT %	NA
	RAPIDLY RENEWABLE CONTENT %	NA
	HARMFUL ADDITIVES	NA
	HARMFUL EMISSIONS	None
	EMISSION STRENGTH OVER TIME	None
	TREATMENTS	NA
	MANUFACTURING	MANUFACTURING PROCESS
HARMFUL EMISSIONS		None
LOCATION OF MANUF. PLANT		Germany
TESTS/CODES		Flammability: CAL 117, NFPA 260 Upholstery California Technical Bulletin #117 Section E - Class 1 (Pass) Direct Glue Wall coverings and Adhered Panels ASTM E 84 (Adhered Mounting Method) - Class A or Class 1 Wrapped Panels and Upholstered Walls ASTM E 84 (Unadhered Mounting Method) - Class A or Class 1 Drapery NFPA 701- Pass
3RD PARTY CERTIFICATION		NA
INSTALLATION		INSTALLATION PROCEDURE
	INSTALLATION ADHESIVES	NA
	UNIT COST	\$12/yd
	LIFE CYCLE ANALYSIS	The product is energy efficient
	EXTRACTION	
	END OF SERVICE LIFE	Last for ever; Exceeds 100,000 double rubs (Wyzenbeek)
MISC. PROPERTIES	QUALITIES/PROPERTIES OF PRODUCT	NA
	MISC. COMMENTS	Width: 54" Repeat: None Weight: 32.78 oz/linear yard
	CONTRIBUTION TO LEED POINTS	NA
COMPANY PROFILE	GREEN PHILOSOPHY	NA
	CONTACT	901 Foch Street Fort Worth, TX 76107 Phone: 817.336.2310 Fax: 817.336.9548 Email: customerservice@anzea.com
MAINTENANCE	AFTER INSTALLATION	W (water based cleaners): To prevent overall soiling, frequent vacuuming or light brushing to remove dust and grime is recommended. Spot clean using the foam only from a water-based cleaning agent such as a mild detergent or non-solvent upholstery shampoo. Apply foam with a soft rag or brush in a circular motion. Vacuum when dry. Always pretest a small area before proceeding.