	[ <b>-</b> v	Lev.
PRODUCT	TYPE OF PRODUCT	Finishes
INFORMATION	COMPANY NAME	A
	COMPANY NAME PRODUCT/COLLECTION NAME	Anzea Truchet
MATERIAL FEEDSTOCK	DESCRIPTION MATERIAL CONTENT	Stain Resist and Light Acrylic Backing 47% Cotton/41% Polyester/12% Nylon
MATERIAL FEEDSTOCK	RECYCLED CONTENT %	NA
	RAPIDLY RENEWABLE CONTENT	NA
	%	I NA
	HARMFUL ADDITIVES	NA
	HARMFUL EMISSIONS	None
	EMISSION STRENGTH OVER TIME	None
	TREATMENTS	NA
MANUFACTURING	MANUFACTURING PROCESS	NA
	HARMFUL EMISSIONS	None
	LOCATION OF MANUF. PLANT	United States
	TESTS/CODES	Flammability:
		CAL 117, NFPA 260
		Upholstery
		California Technical Bulletin #117 Section E - Class 1 (Pass)
		Direct Glue Wall coverings and Adhered Panels
		ASTM E 84 (Adhered Mounting Method) - Class A or Class 1
		Wrapped Panels and Upholstered Walls
		Wiapped i ariels and opnoistered walls
		ASTM E 84 (Unadhered Mounting Method) - Class A or Class 1
		Drapery
		NFPA 701- Pass
	3 <sup>RD</sup> PARTY CERTIFICATION	NA NA
<u>INSTALLATION</u>	INSTALLATION PROCEDURE	NA NA
	INSTALLATION ADHESIVES	NA .
	UNIT COST	\$12/yd
	LIFE CYCLE ANALYSIS	The product is energy efficient
	EXTRACTION	Leating over Everage Of OOO devible with (virgonibaels)
MICC PROPERTIES	END OF SERVICE LIFE	Last for ever; Exceeds 81,000 double rubs (wyzenbeek)
MISC. PROPERTIES	QUALITIES/PROPERTIES OF PRODUCT	NA
	MISC. COMMENTS	Width: 54"
		Repeat: 9"H/9.25"V
		Weight: 12.7 oz/linear yard
	CONTRIBUTION TO LEED POINTS	NA NA
	-	NA
MAINTENANCE	GREEN PHILOSOPHY	
	CONTACT	901 Foch Street
		Fort Worth, TX 76107
		Phone: 817.336.2310
		Fax: 817.336.9548
	AFTER INICTALL ATION	Email: customerservice@anzea.com
	AFTER INSTALLATION	S (solvent or dry cleaning products): To prevent overall soiling, frequent
		vacuuming or light brushing to remove dust and grime is recommended. Spot clean using a mild water-free solvent or dry cleaning product. Clean
		only in a well-ventilated room and avoid any product containing carbon
		tetrachloride, which is highly toxic. Pretest a small area before
		proceeding.