

PRODUCT INFORMATION	TYPE OF PRODUCT	Office furniture
	COMPANY NAME	Steelcase
	PRODUCT/COLLECTION NAME	Series 7
	DESCRIPTION	People are built differently and work differently. Details Height-Adjustable Worksurfaces transform to meet seated and standing needs of everyone from 5' to 6'4".
MATERIAL FEEDSTOCK	MATERIAL CONTENT	FSC or SFI Certified wood and veneer <i>available</i> , water based glue, stain, topcoats and UV finishes. PVC free banding <i>available</i> . 100% recycled particleboard, Steel, Aluminum
	RECYCLED CONTENT %	Steel: The steel used in Details Height-Adjustable Worksurfaces contains between 25% and 30% recycled content. That is broken down as follows: 10% post-consumer waste, approximately 18% pre-consumer waste. Aluminum: The aluminum used in Details Height-Adjustable Worksurfaces contains approximately 60% - 70% recycled content. Post-consumer content is approximately 40% - 50%. Wood: The particle board substrate for Details Height-Adjustable Worksurfaces is 100% recycled wood.
	RAPIDLY RENEWABLE CONTENT %	
	HARMFUL ADDITIVES	Very little – assuming materials are carefully selected. (i.e. Choose PVC free banding)
	HARMFUL EMISSIONS	Low
	EMISSION STRENGTH OVER TIME	Weak
	TREATMENTS	Water based stain, topcoats and UV finishes are used
MANUFACTURING	MANUFACTURING PROCESS	Water from the finishing process is cleaned and reused in continuous loop. A Steelcase owned wind farm supplies energy to a small Texas facility.
	HARMFUL EMISSIONS	Steelcase goes to great lengths to reduce energy consumption and waste. Two facilities are ISO 14001 certified and one in Michigan is LEED certified under the pilot program.
	LOCATION OF MANUF. PLANT	Many locations, the largest are in: Toronto, ON; Grand Rapids, MI; Athens, AL
	TESTS/CODES	ANSI / BIFMA X 5.5 – 2008 Desk /Table Products Tests ANSI / BIFMA X5.9-2004 Storage Products Tests UL 723 Surface Burning Characteristics of Building Materials (ASTM E84 or NFPA 255 test method) UL 1286 Standard for Safety of Office Furnishings Flame Spread Index (FSI) less than 200 Smoke Developed Index (SDI) less than 450 (unless labeled "Smoke Developed Index Over 450")
	3RD PARTY CERTIFICATION	C2C (varies by specific element), BIFMA (a non-profit institutional furniture association)
INSTALLATION	INSTALLATION PROCEDURE	Install via mechanical means as instructed
	INSTALLATION ADHESIVES	N/A
	UNIT COST	Varies
	LIFE CYCLE ANALYSIS EXTRACTION	
	END OF SERVICE LIFE	Steelcase has several end-of-life reclamation programs in place to resell, refurbish, donate, or recycle products.
MISC. PROPERTIES	QUALITIES/PROPERTIES OF PRODUCT	Durable, modular, adaptive
	MISC. COMMENTS	Packaging is returnable/recyclable
	CONTRIBUTION TO LEED POINTS	EA 1.1, 1.2, MR 2, 3.2, 4, 5, 6, 7, EQ 4.4, 4.5, 6.1, 8.1, 8.2, ID 1, 2
COMPANY PROFILE	GREEN PHILOSOPHY	It's possible to find a business partner who cares about the planet. We are constantly seeking more effective ways to conserve resources, prevent pollution and nurture environmental consciousness in our people every day.

MAINTENANCE

CONTACT	1-800-333-9939
AFTER INSTALLATION	Dust with soft damp cloth, - for upholstered surfaces, follow instructions